

Repair & Finishing Compounds

Patch *it*



Rapid Drying Repair Mortar

Ideal for repairing small cracks in walls and floor edges and for creating coves and ramps

- Slump free
- Rapid setting
- Maintains profile
- Smoother to trowel
- Coverage: 3.2m² @ 2mm



Feather *it*



Rapid Drying Finishing Compound

Ideal for use on flooring grade mechanically fixed plywood as well as for filling in gouges and depressions

- Rapid setting
- Rapid drying
- Adhesion without a primer
- Under floor heating
- Coverage as a feather edge: 22m²



Fill *it*



Rapid Setting & Drying Flowable Bulking Concrete

For internal or external backfilling

- Up to 300mm application without bulking aggregates
- Self compacting
- 20 minute set time
- Cover times: 12 hours at 30mm / 24 hours at 300mm
- Coverage: 2.5 x 25kg bags approx 1m² @ 30mm

Primer

Prime *it* Multi-surface Primer



Primer for Porous and Non Porous Substrates

Designed to promote the adhesion of Ultra Floor smoothing underlayments to porous and non porous substrates

- Moisture tolerant
- Enhances adhesion
- Reduces pinholing
- Coverage: 200m² @ 3:1 dilution

Instarmac Group plc

Birch Coppice Business Park,
Danny Morson Way,
Dordon,
Tamworth,
Staffordshire B78 1SE,
United Kingdom

Tel: +44 (0)1827 872244
Fax: +44 (0)1827 874466
Email: enquiries@instarmac.co.uk

Scotland Office:
Tel: +44 (0) 141 613 2144
Email: scotland@instarmac.co.uk

Like us on and find us on
 Follow @Ultra_Floor

**ULTRA
FLOOR**

An **INSTARMAC**® Brand

Contract Flooring Solutions



www.ultra-floor.co.uk

Vers 04.10.16

Smoothing Underlayments
Moisture Protection
Repair & Finishing Compounds
Primer

Smoothing Underlayments

Level *it* Flex



Rapid Drying, Fibre Reinforced Smoothing Underlayment

Ideal for use on substrates where lateral movement and vibration is likely.

- Fibre reinforced
- Unique bag & bottle formulation
- 30 minute walk on time
- Bonded floor coverings after 3 hours, depending on substrate type
- Ideal for electrical underfloor heating
- Minimises cracking
- Coverage: approx 5m² @ 3mm



Level *it* Super30



Rapid Setting, Rapid Drying Smoothing Underlayment

For fast turnaround projects

- Rapid curing
- Extremely smooth finish
- 30 minute walk on time
- Bonded floor coverings after 3 hours
- Loose lay in 45 minutes (unbonded textiles)
- Coverage: approx 5m² @ 3mm



Level *it* Two



High Flow, Two Component Smoothing Underlayment

For commercial or domestic flooring projects

- Versatile
- Bonded floor coverings after 12 hours
- Superior flow
- Moisture tolerant
- Low odour
- Coverage: approx 5m² @ 3mm



Rapid Drying, All Purpose Smoothing Underlayment



For use over adhesive residues

- Foot traffic in as little as 90 minutes
- Ready to receive bonded floor coverings after 4 hours
- Priming not required
- Use over most common subfloors, including old adhesive residues
- Moisture tolerant
- UFH compatible
- Low odour
- Protein free



Smoothing Underlayments

Level *it* Smooth



High Performance, Fine Flow Smoothing Underlayment

For sheet vinyl, LVT, linoleum & rubber

- Extremely smooth finish
- Superior flow
- Pump or trowel applied
- Suitable for underfloor heating systems
- Ideal for large flooring projects
- Coverage: approx 5.5m² @ 3mm



Moisture Protection

DPM *it*



Rapid Curing Primer Membrane

Designed to provide protection against subfloor moisture and as a primer for bonded screed installations.

- Surface DPM
- Two-part epoxy resin system
- Primer for bonded screed applications
- Fast cure system
- Dual chamber packaging



Suppress *it*



Single Component, Two-coat Moisture Vapour Suppressant

Provides a protective primer membrane which suppresses subfloor moisture

- Water based
- Solvent free
- Two-coat application
- Up to 95% RH
- No priming required
- Coverage: approx 16.5m² based on two coats